

LIFT EX[®]

GRI
WE'LL GET YOU THERE

Excellent
run time

Superior
self-cleaning properties

Sturdy
and flexible sidewall

Exceptional
heat dissipation



LIFT EX PNEUMATIC FORKLIFT TIRE

A Pneumatic Material Handling Tire engineered for heavy duty use on forklift trucks and other industrial vehicles. These tires have a large footprint and a tread that assures optimal traction under every condition. The sidewalls are enhanced by multiple layers of reinforcement and a wide rim guard. The augmented contact area and the reinforced sidewall ensures high load carrying capacity.

LIFT EX is best suited for...

- High abrasion resistance
- Maximum stability, safety and comfort
- Heavy Duty Construction
- Extremely low rolling resistance

TECHNICAL DATA

TYRE SIZE	PR	TT / TL	VALVE	Rim				Unloaded Inflated Dimension		LOAD CAPACITY										Inflation Pressure	
										Fork Lift Truck				Other Vehicles				Static Load			
				Up to 15 MPH (A5) / 25 KMPH				5 MPH (A2) / 10 KMPH		15 MPH (A5) / 25 KMPH		0 MPH / 0 KMPH		Max.Load							
				Max.Load		Max.Load		Max.Load		Max.Load		Max.Load									
				Load Wheel		Steering Wheel		Load Wheel		Steering Wheel											
Rec. inch	Alt. inch	± 2 % mm	± 2 % mm	Speed Index	Load Index	(KGS.)	Load Index	(KGS.)	Load Index	(KGS.)	Load Index	(KGS.)	Load Index	(KGS.)	Load Index	(KGS.)	PSI	Bar			
8	5.00-8	8	TT	JS2	3.0D	3.25 I	135	467	A 5	115	1250	106	950	106	950	95	700	122.51	1530	3370	8
	5.00-8	10	TT	JS2	3.0D	3.25 I	135	467	A 5	120	1435	111	1090	111	1090	100	805	127	1755	145	10
	18x7-8	12	TT	V3-02-05	4.33 R	5.00F	173	472	A 5	126	1685	116	1280	116	1280	106	945	133	2061	150	10
	18x7-8	16	TT	V3-02-05	4.33 R	5.00F	173	472	A 5	135	2170	125	1650	125	1650	115	1215	141.69	2657	145	10
	18x7-8	14	TT	V3-02-05	4.33 R	5.00F	173	472	A 5	130	1905	121	1450	121	1450	110	1070	137.2	2335	130	9
9	6.00-9	10	TT	JS2	4.00E		168	536	A 5	127	1735	117	1320	117	1320	107	975	133.93	2125	123	8
	6.00-9	12	TT	JS2	4.00E		168	536	A 5	130	1905	121	1450	121	1450	110	1070	137	2335	130	9
10	6.50-10	10	TT	JS2	5.00F	5.50F	183	592	A 5	131	1970	122	1500	122	1500	111	1105	138	2415	112	8
	6.50-10	12	TT	JS2	5.00F	5.50F	183	592	A 5	134	2150	125	1635	125	1635	114	1205	141	2632	145	10
	6.50-10	14	TT	JS2	5.00F	5.50F	183	592	A 5	138	2365	128	1800	128	1800	118	1325	145	2898	145	10
	23X9-10	20	TT	TR177A	6.5F		236	579	A 5	151	3485	142	2650	142	2650	131	1955	158	4267	145	10
12	7.00-12	12	TT	TR75A	5.00S		196	681	A 5	142	2710	133	2060	133	2060	122	1520	149	3317	123	9
	7.00-12	12HD	TT	TR75A	5.00S		196	681	A 5	142	2715	133	2065	133	2065	122	1520	149	3325	130	9
	7.00-12	14HD	TT	TR75A	5.00S		196	681	A 5	143	2790	134	2120	134	2120	123	1560	150	3413	130	9
	7.00-12	14	TT	TR75A	5.00S		196	681	A 5	143	2790	134	2120	134	2120	123	1560	150	3413	130	9
15	7.00-15	14	TT		5.5	5.50BD	197	762	A 5	159	4405	150	3350	150	3350	139	2470	166	5394	131	9
	8.15-15	14	TT	TR75A	7.0	7.0BD	218	706	A 5	154	3815	145	2900	145	2900	134	2135	161	4669	130	9
	8.15-15	16	TT	TR75A	7.0	7.0BD	218	706	A 5	157	4140	148	3150	148	3150	137	2320	164	5072	120	8
	8.25-15	14	TT	TR177A	6.5	7.0	246	841	A 5	158	4275	149	3250	149	3250	138	2395	165	5233	116	8
	8.25-15	16	TT	TR177A	6.5	7.0	246	841	A 5	161	4670	152	3550	152	3550	141	2615	168	5716	134	9
	250-15	16	TT	TR 77 A	7.5		231	744	A 5	159	4405	150	3350	150	3350	139	2470	166	5394	120	8
	250-15	20	TT	TR 77 A	7.5		231	744	A 5	165	5260	156	4000	156	4000	145	2950	172	6440	152	11
	300-15	18	TT	TR 77 A	8.0		277	851	A 5	170	6080	161	4625	161	4625	150	3410	177	7446	109	8
	300-15	20	TT	TR 77 A	8.0		277	851	A 5	172	6410	163	4875	163	4875	152	3595	179	7849	138	10
20	10.00-20	16	TT		7.5	8.0	285	1080	A 5	173	6575	164	5000	164	5000	153	3685	180	8050	131	9
	10.00-20	18	TT		7.5	8.0	285	1080	A 5	175	6970	166	5300	166	5300	155	3905	182	8533	145	10

OFFICIAL DEALER

ENTYRE bv
 Jolainstraat 45 A B-8554 Sint Denijs
 Tel. +32 (0)56 40 45 79
www.entyre.be

ENTYRE
 MORE THAN JUST TYRES